STATUS: Standard ...


CLASSIFICATION OF EQUIPMENT : Unclassified

USING SERVICE: Navy

DATE OF THIS SHEET: 9 Jun 52

AN/FGC-8

TELETYPEWRITER SET



Teletypewriter Set AN/FGC-8 is general purpose equipment used for the transmission of teletypewriter messages from keyboard or tape and the reception of incoming messages in printed page form. The typing unit and keyboard have standard English characters.

This equipment provides for direct interchange of typewritten telegraph messages, perforation of tape for subsequent transmission, and automatic transmission of printing-telegraph messages under control of perforated tape.

The perforator transmitter keyboard, used in direct sending, may also be operated independently (whether or not receiving an incoming message) as a high speed perforator in the preparation of tape for subsequent transmission.

# AN/FGC-8

TELETYPEWRITER SET

INSTRUCTION LITERATURE:

Teletype Corp Bulletin 4,D1-1 CLASSIFICATION OF EQUIPMENT: Unclassified

USING SERVICE: Navy

DATE OF THIS SHEET: 9 Jun 52

## MAJOR COMPONENTS

QUANT	NAME OF COMPONENT	DIMENSIONS (IN) INSTALLED	WEIGHT (LBS)
gapas	Typing Unit, Teletype Corp Model BP119/210	Not Available	Not Available
Teace and the second	Perforator Transmitter, Teletype Corp Model PEX25JX	तः स	ft 11
and the same	Distributor-Transmitter, Teletype- writer TT-52/FG	11 17	TI FI
1	Power Supply PP-315/GGA-1	$15 \times 25 - 1/2 \times 9 - 3/4$	н

#### **OPERATIONAL CHARACTERISTICS**

TACTICAL USE: Shore stations.

INSTALLATION: Ground, fixed.

CAN COMMUNICATE WITH: Related (or equivalent) terminal and control equipment over wire or

radio facilities and associated apparatus composing the system in

which it is operated.

### TECHNICAL CHARACTERISTICS

OPERATING FUNCTIONS: Standard keyboard operation, friction feed, automatic transmission over

line circuits using perforated tape.

OPERATING SPEED: 72 English characters per line, 368 opm.

MOTOR CHARACTERISTICS: 2,102 rpm, 115 v a-c series-governed.

POWER REQUIREMENTS: 420 w, 115 v, 50/60 cyc, 1 phase ac.

#### PHYSICAL CHARACTERISTICS

Teletypewriter Set AN/FGC-8 measures  $42 \times 36 \times 23$ -1/2 inches, net weight 286 pounds, volume 20.6 cu ft, 0.5 ship ton. Packed for domestic shipment: total weight 447 pounds.