

STATUS: Limited Standard	AN/FGT-TYPE
CLASSIFICATION OF EQUIPMENT: Unclassified	
USING SERVICE: Navy	
DATE OF THIS SHEET: 8 May 52	
	AN/COMP TYPE NUMBER: TT-52/FG
	DISTRIBUTOR-TRANSMITTER, TELETYPEWRITER



TT-52/FG

Distributor-Transmitter, Teletypewriter TT-52/FG is used for the automatic transmission of teletypewriter messages from perforated tape.

It is a general purpose transmitter-distributor designed for table or shelf mounting.

It is part of Teletypewriter Set AN/TGC-3 but may be used separately.

AN/FGT-TYPE		INSTRUCTION LITERATURE: Teletype Bulletin No. 1109	
TT-52/FG		CLASSIFICATION OF EQUIPMENT: Unclassified	
:AN/COMP TYPE NUMBER		USING SERVICE: Navy	
DISTRIBUTOR-TRANSMITTER, TELETYPEWRITER		DATE OF THIS SHEET: 8 May 52	

MAJOR COMPONENTS

QUANT	NAME OF COMPONENT	DIMENSIONS (IN) INSTALLED	(WEIGHT (LBS)
1	Tape Sensing and Transmitter Mechanism	Not Available	Not Available
1	Distributor	" "	" "
1	Motor	" "	" "
1	Cover, Teletype Corp Model 114713AA	9-1/2 x 16-1/4 x 8-3/4	" "

OPERATIONAL CHARACTERISTICS

TACTICAL USE: Shipboard or shore stations.

INSTALLATION: Shipborne, ground.

CAN COMMUNICATE WITH: Any 7.42 unit code teletypewriter receiving equipment geared for 368 OPM.

TECHNICAL CHARACTERISTICS

OPERATING SPEED: 368 opm, approximately 60 wpm.

MOTOR CHARACTERISTICS: Series-governed motor.

POWER REQUIREMENTS: 65 w, 110-115 v, 50/60 cyc, 1 phase, ac.

PHYSICAL CHARACTERISTICS

Information on Distributor-Transmitter, Teletypewriter TT-52/FG not available.